



ARO FDA Stainless Steel Diaphragm Pump

ARO® FDA compliant stainless steel diaphragm pumps deliver safety and quality, as well as industry leading total cost of ownership. By combining the rugged reliability of our EXP pump design with the capacity to handle high volume transfer and dispensing applications, ARO pumps enable you to produce more for your customers.

CE, ATEX, 1935/2004/EC and FDA CFR 21.177

ARO FDA stainless steel pumps are engineered to meet the highest standards and requirements in the industry.



3/4" Metallic Diaphragm Pump

PD07R-XXS-XXX

Maximum Flow gpm (lpm): **13.6 (51.5)**

Maximum Discharge Pressure psi (bar): **100 (6.9)**

Fluid Ports Inlet/Outlet (bsp): **3/4 - 14 N.P.T.F.-2Rp 3/4(3/4-14BSP, parallel)**

Material of Construction: **Aluminum**

Maximum Solids in (mm): **3/32 (2.4)**

Maximum Dry Suction Lift ft (m): **15 (4.5)**



3/4" Aluminum Diaphragm Pump

66607A-XXX-A

Maximum Flow: **33 gpm (125 lpm)**

Maximum Discharge Pressure: **120 psi (8.3 bar)**

Fluid Ports Inlet/Outlet: **3/4 - 14 NPTF-2 Rp 3/4(3/4-14 BSP parallel)**

Material of Construction: **Aluminum**

Maximum Solids: **1/8 inch (3.2 mm)**

Maximum Dry Suction Lift: **17 ft (5.2 m)**



AF0402M Series 4-Ball Piston Pump

- 2:1 Ratio
- Max Flow: 21.3 GPM (80.6 LPM)
- Max Fluid Pressure: 312 psi



650939-X4D-B 2-Ball Pump Piston Pump

- 2.4:1 Ratio
- Max Flow: 4.4 GPM (16.7 LPM)
- Fluid Pressure: 120 - 4800 psi (8.3 - 331.0 bar)